

STANDARD MODELS

Model	Frequency Range	Output Power P _P min / Duty W pk / %	Pulse Width max. **)	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BPA 1011-1250	1 ... 1.1 GHz	1250 / 10	100 µs	61 / 63 ±2	30 / 30	1400	3 HU, 630 mm	29

1 HU = 44.45 mm

STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant)
	P _N -0.5 dB min. at VSWR 2:1
PRF:	1 kHz
Pulse Droop:	1.0 dB max.
Spurious (at P _N):	-60 dBc min. (excluding harmonics)
Class of Operation:	C

GENERAL

RF Input:	N-f, standard on rear panel
RF Output:	N-f, standard on rear panel
Mains Supply:	100 ... 240 V AC, 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-25 ... 85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 G
Cooling:	forced air with integral blower air intake from front, air exhaust at rear

OPTIONS

A) Sample Ports *)	R) RS-232C/RS-485 Remote Control
B) External Dual Directional Coupler	S) Internal RF Switching Unit *)
C) IEEE-488.2 GPIB Remote Control	U) USB Remote Control
D) Front Panel RF-Connectors	W) Liquid Cooling
E) RF Power Indication (digital) *)	X) External Control of other Amplifiers
F) Gain Adjustment *)	

BPA 1 ... 1.1 GHz Pulsed Solid State Amplifiers

G) Output Isolator *)
H) DC-Supply
I) 3x 208 V AC / 60 Hz
L) LAN Remote Control

*) These options may reduce output power and/or gain
**) Optionally other pulse width available