

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 0110-100	9 kHz ... 100 MHz	100 / 125	50 / 52 ±2	20 / 20	400	2 HU, 430 mm	14
BSA 0110-125	9 kHz ... 100 MHz	125 / 150	51 / 53 ±2	20 / 20	500	2 HU, 430 mm	14
BSA 0110-150	9 kHz ... 100 MHz	150 / 175	51.8 / 54 ±2	20 / 20	530	2 HU, 430 mm	15
BSA 0110-200	9 kHz ... 100 MHz	200 / 230	53 / 55 ±2	20 / 20	800	3 HU, 630 mm	27
BSA 0110-250	9 kHz ... 100 MHz	250 / 300	54 / 56 ±2	20 / 20	900	3 HU, 630 mm	28
BSA 0110-400	9 kHz ... 100 MHz	400 / 440	56 / 58 ±2	20 / 20	1700	4 HU, 630 mm	37
BSA 0110-500	9 kHz ... 100 MHz	500 / 600	57 / 59 ±2	20 / 18	2100	4 HU, 630 mm	37
BSA 0110-600	9 kHz ... 100 MHz	600 / 700	57.8 / 60 ±2	20 / 18	2500	5 HU, 630 mm	58
BSA 0110-1000	9 kHz ... 100 MHz	1000 / 1200	60 / 62 ±2	20 / 18	3100	5 HU, 630 mm	59
BSA 0110-1500	9 kHz ... 100 MHz	1500 / 1700	61.8 / 64 ±2	20 / 18	10000	15 HU, 630 mm	200
BSA 0110-3000	9 kHz ... 100 MHz	3000 / 3300	64.8 / 67 ±2	20 / 20	14000	24 HU, 800 mm	265
BSA 0110-5000	9 kHz ... 100 MHz	5000 / 5500	67 / 69 ±2	20 / 20	30000	37 HU, 800 mm (XL)	600
BSA 0110-10000	9 kHz ... 100 MHz	10000 / 11000	70 / 72 ±2	20 / 20	55000	2x 37 HU, 800 mm (XL)	1100
BSA 0110-12000	9 kHz ... 100 MHz	12000 / 13000	70.8 / 73 ±2	20 / 20	55000	2x 37 HU, 800 mm (XL)	1100

For individual data sheets, please click on the above model name

1 HU = 44.45 mm