

STANDARDMODELLE

| Modell | Frequenzbereich | Ausgangsleistung | Verstärkung | Harmonische | Netzleistung | Abmessungen | Gewicht |
|-------------------|----------------------|----------------------|-----------------|------------------|--------------|----------------------|---------|
| | | P_N min / typ W | min / typ dB | 2te / 3te dBc | VA | (H, T) 19"-System | |
| BSA 1001-30D | 100 kHz ... 1000 MHz | | | | 250 | 2 HE, 430 mm | 15 |
| | 100 kHz ... 100 MHz | 30 / 35 | 44,8 / 47 ±2 | 20 / 20 | | | |
| | 100 ... 1000 MHz | 30 / 35 | 44,8 / 47 ±2 | 20 / 20 | | | |
| BSA 1001-50/75D | 100 kHz ... 1000 MHz | | | | 600 | 3 HE, 630 mm | 24 |
| | 100 kHz ... 400 MHz | 50 / 70 | 47 / 49 ±2 | 20 / 20 | | | |
| | 400 ... 1000 MHz | 75 / 100 | 48,8 / 51 ±2 | 20 / 20 | | | |
| BSA 1001-75D | 100 kHz ... 1000 MHz | | | | 600 | 3 HE, 630 mm | 24 |
| | 100 kHz ... 400 MHz | 75 / 100 | 48,8 / 51 ±2 | 20 / 20 | | | |
| | 400 ... 1000 MHz | 75 / 100 | 48,8 / 51 ±2 | 20 / 20 | | | |
| BSA 1001-100D | 100 kHz ... 1000 MHz | | | | 550 | 3 HE, 630 mm | 24 |
| | 100 kHz ... 400 MHz | 100 / 120 | 50 / 52 ±2 | 20 / 20 | | | |
| | 400 ... 1000 MHz | 100 / 120 | 50 / 52 ±2 | 20 / 20 | | | |
| BSA 1001-150/100D | 100 kHz ... 1000 MHz | | | | 700 | 3 HE, 630 mm | 24 |
| | 100 kHz ... 400 MHz | 150 / 170 | 51,8 / 54 ±2 | 20 / 20 | | | |
| | 400 ... 1000 MHz | 100 / 120 | 50 / 52 ±2 | 20 / 20 | | | |
| BSA 1001-250D | 100 kHz ... 1000 MHz | | | | 2100 | 4 HE, 630 mm | 45 |
| | 100 kHz ... 400 MHz | 250 / 300 | 54 / 56 ±2 | 20 / 20 | | | |
| | 400 ... 1000 MHz | 250 / 300 | 54 / 56 ±2 | 20 / 20 | | | |
| BSA 1001-300D | 100 kHz ... 1000 MHz | | | | 2200 | 4 HE, 630 mm | 46 |
| | 100 kHz ... 400 MHz | 300 / 350 | 54,8 / 57 ±2 | 20 / 20 | | | |
| | 400 ... 1000 MHz | 300 / 330 | 54,8 / 57 ±2 | 20 / 20 | | | |
| BSA 1001-500/300D | 100 kHz ... 1000 MHz | | | | 2500 | 4 HE, 630 mm | 46 |
| | 100 kHz ... 250 MHz | 500 / 550 | 57 / 59 ±2 | 20 / 18 | | | |
| | 250 ... 400 MHz | 300 / 350 | 54,8 / 57 ±2 | 20 / 20 | | | |
| | 400 ... 1000 MHz | 300 / 350 | 54,8 / 57 ±2 | 20 / 20 | | | |

Für Einzeldatenblätter klicken Sie bitte auf die obige Modellbezeichnung

1 HE = 44,45 mm