

STANDARDMODELLE

Modell	Frequenzbereich	Ausgangsleistung	Verstärkung	Harmonische	Netzleistung	Abmessungen	Gewicht
		P_N min / typ W	min / typ dB	2te / 3te dBc	VA	(H, T) 19"-System	
BSA 1001-30D	100 kHz ... 1000 MHz				250	2 HE, 430 mm	15
	100 kHz ... 100 MHz	30 / 35	44,8 / 47 ±2	20 / 20			
	100 ... 1000 MHz	30 / 35	44,8 / 47 ±2	20 / 20			
BSA 1001-50/75D	100 kHz ... 1000 MHz				480	3 HE, 630 mm	22
	100 kHz ... 400 MHz	50 / 70	47 / 49 ±2	20 / 20			
	400 ... 1000 MHz	75 / 100	48,8 / 51 ±2	20 / 20			
BSA 1001-75D	100 kHz ... 1000 MHz				600	3 HE, 630 mm	23
	100 kHz ... 400 MHz	75 / 100	48,8 / 51 ±2	20 / 20			
	400 ... 1000 MHz	75 / 100	48,8 / 51 ±2	20 / 20			
BSA 1001-100D	100 kHz ... 1000 MHz				650	3 HE, 630 mm	23
	100 kHz ... 400 MHz	100 / 120	50 / 52 ±2	20 / 20			
	400 ... 1000 MHz	100 / 120	50 / 52 ±2	20 / 20			
BSA 1001-150/100D	100 kHz ... 1000 MHz				700	3 HE, 630 mm	24
	100 kHz ... 400 MHz	150 / 170	51,8 / 54 ±2	20 / 20			
	400 ... 1000 MHz	100 / 120	50 / 52 ±2	20 / 20			
BSA 1001-250D	100 kHz ... 1000 MHz				2100	4 HE, 630 mm	45
	100 kHz ... 400 MHz	250 / 300	54 / 56 ±2	20 / 20			
	400 ... 1000 MHz	250 / 300	54 / 56 ±2	20 / 20			
BSA 1001-300D	100 kHz ... 1000 MHz				2200	4 HE, 630 mm	46
	100 kHz ... 400 MHz	300 / 350	54,8 / 57 ±2	20 / 20			
	400 ... 1000 MHz	300 / 330	54,8 / 57 ±2	20 / 20			
BSA 1001-500/300D	100 kHz ... 1000 MHz				2500	4 HE, 630 mm	46
	100 kHz ... 250 MHz	500 / 550	57 / 59 ±2	20 / 18			
	250 ... 400 MHz	300 / 350	54,8 / 57 ±2	20 / 20			
	400 ... 1000 MHz	300 / 350	54,8 / 57 ±2	20 / 20			

Für Einzeldatenblätter klicken Sie bitte auf die obige Modellbezeichnung

1 HE = 44,45 mm