

STANDARDMODELLE

| Modell | Frequenzbereich | Ausgangsleistung | Verstärkung | Harmonische | Netzleistung | Abmessungen | Gewicht |
|---------------------|-------------------|----------------------|-----------------|------------------|--------------|----------------------|---------|
| | | P_N min / typ W | min / typ dB | 2te / 3te dBc | VA | (H, T) 19"-System | |
| BSA 0125-5 | 9 kHz ... 250 MHz | 5 / 8 | 37 / 39 ±2 | 20 / 20 | 110 | 2 HE, 430 mm | 10 |
| BSA 0125-15 | 9 kHz ... 250 MHz | 15 / 25 | 41,8 / 44 ±2 | 20 / 20 | 175 | 2 HE, 430 mm | 12 |
| BSA 0125-25 | 9 kHz ... 250 MHz | 25 / 30 | 44 / 46 ±2 | 20 / 20 | 180 | 2 HE, 430 mm | 12 |
| BSA 0125-75 | 9 kHz ... 250 MHz | 75 / 100 | 48,8 / 51 ±2 | 20 / 20 | 340 | 2 HE, 430 mm | 14 |
| BSA 0125-125 | 9 kHz ... 250 MHz | 125 / 150 | 51 / 53 ±2 | 20 / 20 | 530 | 2 HE, 430 mm | 14 |
| BSA 0125-150 | 9 kHz ... 250 MHz | 150 / 200 | 51,8 / 54 ±2 | 20 / 20 | 550 | 2 HE, 430 mm | 15 |
| BSA 0125-200 | 9 kHz ... 250 MHz | 200 / 220 | 53 / 55 ±2 | 20 / 20 | 800 | 3 HE, 630 mm | 21 |
| BSA 0125-250 | 9 kHz ... 250 MHz | 250 / 300 | 54 / 56 ±2 | 20 / 18 | 800 | 3 HE, 630 mm | 21 |
| BSA 0125-300 | 9 kHz ... 250 MHz | 300 / 350 | 54 / 56 ±2 | 20 / 20 | 1000 | 3 HE, 630 mm | 34 |
| BSA 0125-400 | 9 kHz ... 250 MHz | 400 / 500 | 56 / 58 ±2 | 20 / 20 | 1900 | 4 HE, 630 mm | 37 |
| BSA 0125-500 | 9 kHz ... 250 MHz | 500 / 600 | 57 / 59 ±2 | 20 / 18 | 2000 | 4 HE, 630 mm | 37 |
| BSA 0125-600 | 9 kHz ... 250 MHz | 600 / 650 | 57,8 / 60 ±2 | 20 / 17 | 2400 | 4 HE, 630 mm | 38 |
| BSA 0125-800 | 9 kHz ... 250 MHz | 800 / 900 | 59 / 61 ±2 | 20 / 20 | 3100 | 5 HE, 630 mm | 59 |
| BSA 0125-1000/800 | 9 kHz ... 250 MHz | | | | 3100 | 5 HE, 630 mm | 59 |
| | 9 kHz ... 200 MHz | 1000 / 1200 | 60 / 62 ±2 | 20 / 20 | | | |
| | 200 ... 250 MHz | 800 / 1000 | 59 / 61 ±2 | 20 / 20 | | | |
| BSA 0125-1000 | 9 kHz ... 250 MHz | 1000 / 1100 | 60 / 62 ±2 | 20 / 18 | 3100 | 5 HE, 630 mm | 59 |
| BSA 0125-1250 | 9 kHz ... 250 MHz | 1250 / 1350 | 61 / 63 ±2 | 20 / 20 | 6300 | 15 HE, 630 mm | 175 |
| BSA 0125-2000 | 9 kHz ... 250 MHz | 2000 / 2200 | 63 / 65 ±2 | 20 / 18 | 11500 | 24 HE, 800 mm | 245 |
| BSA 0125-2000W | 9 kHz ... 250 MHz | 2000 / 2200 | 63 / 65 ±2 | 20 / 18 | 11500 | 24 HE, 800 mm | 245 |
| BSA 0125-2500 | 9 kHz ... 250 MHz | 2500 / 2700 | 64 / 66 ±2 | 20 / 18 | 11500 | 24 HE, 800 mm | 265 |
| BSA 0125-3000/2500 | 9 kHz ... 250 MHz | | | | 11500 | 24 HE, 800 mm | 265 |
| | 9 kHz ... 200 MHz | 3000 / 3300 | 64,8 / 67 ±2 | 20 / 20 | | | |
| | 200 ... 250 MHz | 2500 / 2800 | 64 / 66 ±2 | 20 / 20 | | | |
| BSA 0125-3000/2500W | 9 kHz ... 250 MHz | | | | 11500 | 18 HE, 800 mm | 265 |
| | 9 kHz ... 200 MHz | 3000 / 3300 | 64,8 / 67 ±2 | 20 / 20 | | | |
| | 200 ... 250 MHz | 2500 / 2800 | 64 / 66 ±2 | 20 / 20 | | | |

BSA 9 kHz ... 250 MHz Halbleiterverstärker

| Modell | Frequenzbereich | Ausgangsleistung | Verstärkung | Harmonische | Netzleistung | Abmessungen | Gewicht |
|---------------------|-------------------|----------------------|-----------------|------------------|--------------|----------------------|---------|
| | | P_N min / typ W | min / typ dB | 2te / 3te dBc | VA | (H, T) 19"-System | |
| BSA 0125-5000/4000 | 9 kHz ... 250 MHz | | | | 30000 | 37 HE, 800 mm (XL) | 600 |
| | 9 kHz ... 100 MHz | 5000 / 5500 | 67 / 70 ±3 | 20 / 20 | | | |
| | 100 ... 250 MHz | 4000 / 5000 | 67 / 70 ±3 | 20 / 20 | | | |
| BSA 0125-5000/4000W | 9 kHz ... 250 MHz | | | | 30000 | 37 HE, 800 mm | 600 |
| | 9 kHz ... 100 MHz | 5000 / 5500 | 67 / 70 ±3 | 20 / 20 | | | |
| | 100 ... 250 MHz | 4000 / 5000 | 67 / 70 ±3 | 20 / 20 | | | |

Für Einzeldatenblätter klicken Sie bitte auf die obige Modellbezeichnung

1 HE = 44,45 mm