

STANDARDMODELLE

Modell	Frequenzbereich	Ausgangsleistung	Verstärkung	Harmonische	Netzleistung	Abmessungen	Gewicht
		$P_N$ min / typ W	min / typ dB	2te / 3te dBc	VA	(H, T) 19"-System	
BLMA 1060-0.5	1 ... 6 GHz	0,5 / 0,6	27 / 29 ±2	20 / 20	50	2 HE, 430 mm	10
BLMA 1060-1	1 ... 6 GHz	1 / 1,2	30 / 32 ±2	20 / 20	50	2 HE, 430 mm	10
BLMA 1060-2	1 ... 6 GHz	2 / 2,5	33 / 35 ±2	20 / 20	70	2 HE, 430 mm	10
BLMA 1060-3	1 ... 6 GHz	3 / 3,3	34,8 / 37 ±2	20 / 20	90	2 HE, 430 mm	10
BLMA 1060-6	1 ... 6 GHz	6 / 10	37,8 / 40 ±2	15 / 20	160	2 HE, 430 mm	10
BLMA 1060-10	1 ... 6 GHz	10 / 15	40 / 42 ±2	15 / 20	200	2 HE, 430 mm	11
BLMA 1060-15	1 ... 6 GHz	15 / 20	41,8 / 45 ±3	20 / 20	250	2 HE, 430 mm	12
BLMA 1060-25	1 ... 6 GHz	25 / 30	44 / 47 ±3	18 / 20	450	2 HE, 430 mm	13
BLMA 1060-30	1 ... 6 GHz	30 / 35	44,8 / 48 ±3	18 / 20	550	2 HE, 430 mm	14
BLMA 1060-50	1 ... 6 GHz	50 / 70	47 / 50 ±3	18 / 20	550	2 HE, 430 mm	14
BLMA 1060-75	1 ... 6 GHz	75 / 80	48,8 / 52 ±3	18 / 20	950	3 HE, 430 mm	22
BLMA 1060-100	1 ... 6 GHz	100 / 120	50 / 53 ±3	15 / 20	1050	3 HE, 430 mm	22
BLMA 1060-150	1 ... 6 GHz	150 / 180	51,8 / 55 ±2	20 / 20	2000	4 HE, 630 mm	41
BLMA 1060-200/100	1 ... 6 GHz				2000	4 HE, 630 mm	40
	1 ... 2 GHz	200 / 240	53 / 55 ±2	15 / 20			
	2 ... 4 GHz	180 / 240	53 / 55 ±2	20 / 20			
	4 ... 6 GHz	100 / 120	50 / 52 ±2	20 / 20			
BLMA 1060-200	1 ... 6 GHz	200 / 220	53 / 56 ±3	20 / 20	3100	5 HE, 630 mm	63
BLMA 1060-200DS	1 ... 6 GHz				3000	12 HE, 800 mm	110
	1 ... 2,5 GHz	200 / 240	53 / 55 ±2	20 / 20			
	2,5 ... 6 GHz	200 / 240	53 / 55 ±2	15 / 20			
BLMA 1060-250	1 ... 6 GHz	250 / 280	54 / 57 ±3	20 / 20	4500	7 HE, 630 mm	85
BLMA 1060-300/150/100D	1 ... 6 GHz				2500	6 HE, 630 mm	67
	1 ... 2,5 GHz	300 / 320	54,8 / 57 ±2	15 / 20			
	2,5 ... 4 GHz	150 / 170	51,8 / 54 ±2	20 / 20			
	4 ... 6 GHz	100 / 120	50 / 52 ±2	20 / 20			
BLMA 1060-300/200	1 ... 6 GHz				3200	5 HE, 630 mm	55
	1 ... 4 GHz	300 / 350	54,8 / 58 ±3	20 / 20			
	4 ... 6 GHz	200 / 220	53 / 56 ±3	20 / 20			

# BLMA 1 ... 6 GHz Halbleiterverstärker

Modell	Frequenzbereich	Ausgangsleistung $P_N$ min / typ W	Verstärkung min / typ dB	Harmonische 2te / 3te dBc	Netzleistung VA	Abmessungen (H, T) 19"-System	Gewicht kg
BLMA 1060-300	1 ... 6 GHz	300 / 320	54,8 / 58 ±3	20 / 20	5000	7 HE, 630 mm	85
BLMA 1060-400/100D	1 ... 6 GHz				4200	8 HE, 630 mm	98
	1 ... 4 GHz	400 / 450	56 / 59 ±3	20 / 20			
	4 ... 6 GHz	100 / 120	50 / 53 ±3	20 / 20			
BLMA 1060-400	1 ... 6 GHz	400 / 450	56 / 59 ±3	20 / 20	6500	10 HE, 630 mm	121
BLMA 1060-500	1 ... 6 GHz	500 / 550	57 / 60 ±3	18 / 20	7000	12 HE, 800 mm	153
BLMA 1060-750	1 ... 6 GHz	750 / 800	58,8 / 62 ±3	15 / 20	10000	18 HE, 800 mm	190
BLMA 1060-1000/300D	1 ... 6 GHz				13500	24 HE, 800 mm	260
	1 ... 3,2 GHz	1000 / 1100	60 / 63 ±3	15 / 20			
	3,2 ... 6 GHz	300 / 350	54,8 / 58 ±3	15 / 20			
BLMA 1060-1000	1 ... 6 GHz	1000 / 1100	60 / 63 ±3	15 / 20	15000	24 HE, 800 mm	260

Für Einzeldatenblätter klicken Sie bitte auf die obige Modellbezeichnung

1 HE = 44,45 mm