

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 0140-5	9 kHz ... 400 MHz	5 / 8	37 / 39 ±2	20 / 20	100	2 HU, 430 mm	10
BSA 0140-10	9 kHz ... 400 MHz	10 / 15	40 / 42 ±2	20 / 20	150	2 HU, 430 mm	12
BSA 0140-20	9 kHz ... 400 MHz	20 / 25	43 / 45 ±2	20 / 20	180	2 HU, 430 mm	13
BSA 0140-40	9 kHz ... 400 MHz	40 / 50	46 / 48 ±2	20 / 20	350	2 HU, 430 mm	13
BSA 0140-75	9 kHz ... 400 MHz	75 / 100	48.8 / 51 ±2	20 / 20	480	2 HU, 430 mm	14
BSA 0140-100	9 kHz ... 400 MHz	100 / 120	50 / 52 ±2	20 / 20	560	2 HU, 430 mm	16
BSA 0140-150	9 kHz ... 400 MHz	150 / 200	51.8 / 54 ±2	20 / 20	850	3 HU, 630 mm	18
BSA 0140-200	9 kHz ... 400 MHz	200 / 250	53 / 55 ±2	20 / 20	1300	3 HU, 630 mm	27
BSA 0140-250	9 kHz ... 400 MHz	250 / 280	54 / 56 ±2	20 / 20	1500	3 HU, 630 mm	34
BSA 0140-400	9 kHz ... 400 MHz	400 / 450	56 / 58 ±2	20 / 20	3100	5 HU, 630 mm	59
BSA 0140-500/250	9 kHz ... 400 MHz				2500	5 HU, 630 mm	58
	9 kHz ... 250 MHz	500 / 600	57 / 59 ±2	20 / 20			
	250 ... 400 MHz	250 / 300	54 / 56 ±2	20 / 20			
BSA 0140-500D	9 kHz ... 400 MHz				2800	9 HU, 630 mm	85
	9 kHz ... 100 MHz	500 / 600	57 / 59 ±2	20 / 20			
	100 ... 400 MHz	500 / 600	57 / 59 ±2	20 / 20			

For individual data sheets, please click on the above model name

1 HU = 44.45 mm