

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLMA 0830-1	0.8 ... 3 GHz	1 / 1.3	30 / 32 ±2	20 / 20	75	2 HU, 430 mm	11
BLMA 0830-3	0.8 ... 3 GHz	3 / 3.5	34.8 / 37 ±2	20 / 20	75	2 HU, 430 mm	12
BLMA 0830-6	0.8 ... 3 GHz	6 / 7	37.8 / 40 ±2	20 / 20	100	2 HU, 430 mm	12
BLMA 0830-10	0.8 ... 3 GHz	10 / 13	40 / 43 ±3	15 / 20	180	2 HU, 430 mm	13
BLMA 0830-20	0.8 ... 3 GHz	20 / 25	43 / 45 ±2	15 / 20	250	2 HU, 430 mm	13
BLMA 0830-40	0.8 ... 3 GHz	40 / 50	46 / 48 ±2	12 / 20	250	3 HU, 430 mm	18
BLMA 0830-80	0.8 ... 3 GHz	80 / 100	49 / 51 ±2	20 / 20	450	3 HU, 430 mm	18
BLMA 0830-100	0.8 ... 3 GHz	100 / 120	50 / 52 ±2	15 / 20	500	3 HU, 430 mm	18
BLMA 0830-150	0.8 ... 3 GHz	150 / 180	51.8 / 54 ±2	15 / 20	1200	3 HU, 630 mm	30
BLMA 0830-200	0.8 ... 3 GHz	200 / 230	53 / 55 ±2	15 / 20	1600	4 HU, 630 mm	38
BLMA 0830-250	0.8 ... 3 GHz	250 / 300	54 / 56 ±2	20 / 20	1800	4 HU, 630 mm	39
BLMA 0830-500	0.8 ... 3 GHz	500 / 550	57 / 59 ±2	15 / 20	3500	8 HU, 630 mm	73

For individual data sheets, please click on the above model name

1 HU = 44.45 mm