

STANDARD MODELS

| Model | Frequency Range | Output Power P_N min / typ W | Gain min / typ dB | Harmonics 2nd / 3rd dBc | Line Power VA | Dimensions (H, D) 19"-System | Weight kg |
|----------------|-----------------|--------------------------------------|-------------------------|-------------------------------|------------------|------------------------------------|--------------|
| TWAL 0208-1000 | 2.5 ... 7.5 GHz | 1000 / 1100 | 60 / 65 ±5 | 5 / 20 | 6000 | 12 HU, 800 mm | 100 |

1 HU = 44.45 mm

STANDARD SPECIFICATIONS

| | |
|-----------------------|---|
| Input Power: | 0 dBm (1 mW) max. |
| Overdrive Protection: | up to +10 dBm for no damage |
| Input Impedance: | 50 Ohm nominal |
| Output Impedance: | 50 Ohm nominal |
| Input VSWR: | <2:1 typ. |
| Load VSWR: | infinite for no damage (100% mismatch tolerant) |
| | P_N -0.5 dB min. at VSWR 2:1 |
| Spurious (at P_N): | -60 dBc min. (excluding harmonics) |
| Noise Figure | 20 dB max. |
| Class of Operation: | A-linear |

GENERAL

| | |
|----------------------|---|
| RF Input: | N-f, standard on rear panel |
| RF Output: | 7-16-f, standard on rear panel |
| Mains Supply: | 3x 400 V AC ±10%, 47 ... 63 Hz |
| Elapsed Time Meter: | via status display |
| Ambient Temperature: | 0 ... +45 °C |
| Storage Temperature: | -25 ... +85 °C |
| Relative Humidity: | up to 95% (non-condensing) |
| Operating Altitude: | up to 2000 m above sea level |
| Vibration and Shock: | normal laboratory environment |
| Cooling: | forced air with integral blower air intake and exhaust at rear Option W: Liquid cooling External heat exchanger required |

OPTIONS

| | |
|--------------------------------------|----------------------------------|
| A) RF Monitor Outputs *) | N) Harmonic Filter *) |
| B) External Dual Directional Coupler | R) RS-232C/RS-485 Remote Control |
| C) IEEE-488.2 GPIB Remote Control | S) Internal RF Switching Unit *) |
| D) Front Panel RF Connectors | U) USB Remote Control |
| E) RF Power Indication (digital) *) | W) Liquid Cooling |

TWAL 2 ... 8 GHz TWT Amplifiers

F) Gain Adjustment *)
G) Output Isolator *)
L) Remote Control

X) External Control of other Amplifiers

*) These options may reduce output power and/or gain