

STANDARD MODELS

| Model         | Frequency Range     | Output Power<br>$P_N$ min / typ<br>W | Gain<br>min / typ<br>dB | Harmonics<br>2nd / 3rd<br>dBc | Line Power<br>VA | Dimensions<br>(H, D)<br>19"-System | Weight<br>kg |
|---------------|---------------------|--------------------------------------|-------------------------|-------------------------------|------------------|------------------------------------|--------------|
| BSA 1010-10   | 100 kHz ... 100 MHz | 10 / 15                              | 40 / 42 ±2              | 20 / 20                       | 150              | 2 HU, 430 mm                       | 10           |
| BSA 1010-30   | 100 kHz ... 100 MHz | 30 / 35                              | 44.8 / 47 ±2            | 20 / 20                       | 350              | 2 HU, 430 mm                       | 13           |
| BSA 1010-50   | 100 kHz ... 100 MHz | 50 / 70                              | 47 / 49 ±2              | 20 / 18                       | 380              | 2 HU, 430 mm                       | 13           |
| BSA 1010-125  | 100 kHz ... 100 MHz | 125 / 140                            | 51 / 53 ±2              | 20 / 20                       | 550              | 2 HU, 430 mm                       | 13           |
| BSA 1010-150  | 100 kHz ... 100 MHz | 150 / 200                            | 51.8 / 54 ±2            | 20 / 20                       | 600              | 3 HU, 630 mm                       | 17           |
| BSA 1010-250  | 100 kHz ... 100 MHz | 250 / 280                            | 54 / 56 ±2              | 20 / 20                       | 900              | 3 HU, 630 mm                       | 29           |
| BSA 1010-500  | 100 kHz ... 100 MHz | 500 / 600                            | 57 / 59 ±2              | 20 / 20                       | 2800             | 5 HU, 630 mm                       | 45           |
| BSA 1010-600  | 100 kHz ... 100 MHz | 600 / 750                            | 57.8 / 60 ±2            | 20 / 20                       | 3000             | 5 HU, 630 mm                       | 45           |
| BSA 1010-1000 | 100 kHz ... 100 MHz | 1000 / 1700                          | 60 / 62 ±2              | 20 / 20                       | 5500             | 15 HU, 630 mm                      | 140          |
| BSA 1010-1200 | 100 kHz ... 100 MHz | 1200 / 1300                          | 60.8 / 63 ±2            | 20 / 20                       | 6000             | 18 HU, 800 mm                      | 175          |
| BSA 1010-1500 | 100 kHz ... 100 MHz | 1500 / 1700                          | 61.8 / 64 ±2            | 20 / 20                       | 10000            | 24 HU, 800 mm                      | 290          |

For individual data sheets, please click on the above model name

1 HU = 44.45 mm