

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 1001-30D	100 kHz ... 1000 MHz				360	2 HU, 430 mm	15
	100 kHz ... 100 MHz	30 / 35	44.8 / 47 ±2	25 / 20			
	100 ... 1000 MHz	30 / 35	44.8 / 47 ±2	25 / 20			
BSA 1001-50/75D	100 kHz ... 1000 MHz				600	3 HU, 630 mm	26
	100 kHz ... 400 MHz	50 / 70	47 / 49 ±2	20 / 20			
	400 ... 1000 MHz	75 / 100	48.8 / 51 ±2	20 / 20			
BSA 1001-75D	100 kHz ... 1000 MHz				600	3 HU, 630 mm	26
	100 kHz ... 400 MHz	75 / 100	48.8 / 51 ±2	20 / 20			
	400 ... 1000 MHz	75 / 100	48.8 / 51 ±2	20 / 20			
BSA 1001-100D	100 kHz ... 1000 MHz				550	3 HU, 630 mm	25
	100 kHz ... 400 MHz	100 / 120	50 / 52 ±2	20 / 20			
	400 ... 1000 MHz	100 / 120	50 / 52 ±2	20 / 20			
BSA 1001-150/125D	100 kHz ... 1000 MHz				900	3 HU, 630 mm	35
	100 kHz ... 400 MHz	150 / 170	51.8 / 54 ±2	20 / 20			
	400 ... 1000 MHz	125 / 140	51 / 53 ±2	20 / 20			
BSA 1001-250D	100 kHz ... 1000 MHz				1800	5 HU, 630 mm	45
	100 kHz ... 400 MHz	250 / 300	54 / 56 ±2	20 / 20			
	400 ... 1000 MHz	250 / 300	54 / 56 ±2	20 / 20			
BSA 1001-300/250D	100 kHz ... 1000 MHz				2000	8 HU, 630 mm	81
	100 kHz ... 400 MHz	300 / 350	54.8 / 57 ±2	20 / 20			
	400 ... 1000 MHz	250 / 300	54 / 56 ±2	20 / 20			
BSA 1001-500/300D	100 kHz ... 1000 MHz				2200	8 HU, 630 mm	81
	100 kHz ... 250 MHz	500 / 550	57 / 59 ±2	20 / 20			
	250 ... 400 MHz	300 / 350	54.8 / 57 ±2	20 / 20			
	400 ... 1000 MHz	300 / 350	54.8 / 57 ±2	20 / 20			

For individual data sheets, please click on the above model name

1 HU = 44.45 mm