

STANDARD MODELS

Model	Frequency Range	Output Power $P_N$ min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLMA 2040-1	2 ... 4 GHz	1 / 1.3	30 / 32 ±2	20 / 20	50	2 HU, 430 mm	11
BLMA 2040-2	2 ... 4 GHz	2 / 2.5	33 / 35 ±2	20 / 20	50	2 HU, 430 mm	11
BLMA 2040-7	2 ... 4 GHz	7 / 9	38.5 / 41 ±2	20 / 20	75	2 HU, 430 mm	11
BLMA 2040-20	2 ... 4 GHz	20 / 25	43 / 45 ±2	20 / 20	200	2 HU, 430 mm	12
BLMA 2040-35	2 ... 4 GHz	35 / 45	45.4 / 48 ±2	20 / 20	400	3 HU, 630 mm	12
BLMA 2040-60	2 ... 4 GHz	60 / 75	47.8 / 50 ±2	20 / 20	600	3 HU, 630 mm	26
BLMA 2040-80S	2 ... 4 GHz	80 / 100	49 / 51 ±2	15 / 20	650	3 HU, 630 mm	21
BLMA 2040-110	2 ... 4 GHz	110 / 130	50.4 / 53 ±2	20 / 20	1100	3 HU, 630 mm	27
BLMA 2040-200	2 ... 4 GHz	200 / 240	53 / 55 ±2	20 / 20	2500	6 HU, 630 mm	45
BLMA 2040-300	2 ... 4 GHz	300 / 350	54.8 / 57 ±2	20 / 20	4000	12 HU, 800 mm	120
BLMA 2040-400	2 ... 4 GHz	400 / 450	56 / 58 ±2	20 / 20	7000	8 HU, 630 mm	88

For individual data sheets, please click on the above model name

1 HU = 44.45 mm