

STANDARD MODELS

| Model | Frequency Range | Output Power P_N min / typ W | Gain min / typ dB | Harmonics 2nd / 3rd dBc | Line Power VA | Dimensions (H, D) 19"-System | Weight kg |
|------------------|---------------------|--------------------------------------|-------------------------|-------------------------------|------------------|------------------------------------|--------------|
| BSA 1050-50 | 100 kHz ... 500 MHz | 50 / 70 | 47 / 49 ±2 | 20 / 20 | 600 | 3 HU, 630 mm | 19 |
| BSA 1050-100 | 100 kHz ... 500 MHz | 100 / 120 | 50 / 52 ±2 | 20 / 20 | 700 | 3 HU, 630 mm | 20 |
| BSA 1050-150 | 100 kHz ... 500 MHz | 150 / 180 | 51.8 / 54 ±2 | 20 / 18 | 800 | 3 HU, 630 mm | 20 |
| BSA 1050-300/100 | 100 kHz ... 500 MHz | | | | 2200 | 4 HU, 630 mm | 40 |
| | 100 kHz ... 400 MHz | 300 / 350 | 54.8 / 57 ±2 | 20 / 20 | | | |
| | 400 ... 500 MHz | 100 / 150 | 50 / 52 ±2 | 20 / 20 | | | |
| BSA 1050-500/100 | 100 kHz ... 500 MHz | | | | 2500 | 4 HU, 630 mm | 38 |
| | 100 kHz ... 250 MHz | 500 / 600 | 57 / 59 ±2 | 20 / 17 | | | |
| | 250 ... 400 MHz | 300 / 350 | 54.8 / 57 ±2 | 20 / 20 | | | |
| | 400 ... 500 MHz | 100 / 120 | 50 / 52 ±2 | 20 / 20 | | | |

For individual data sheets, please click on the above model name

1 HU = 44.45 mm