

STANDARD MODELS

Model	Frequency Range	Output Power $P_N$ min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 0125-5	9 kHz ... 250 MHz	5 / 8	37 / 39 ±2	20 / 20	100	2 HU, 430 mm	10
BSA 0125-15	9 kHz ... 250 MHz	15 / 25	41.8 / 44 ±2	20 / 20	175	2 HU, 430 mm	12
BSA 0125-25	9 kHz ... 250 MHz	25 / 30	44 / 46 ±2	20 / 20	300	2 HU, 430 mm	12
BSA 0125-75	9 kHz ... 250 MHz	75 / 100	48.8 / 51 ±2	20 / 20	380	2 HU, 430 mm	13
BSA 0125-125	9 kHz ... 250 MHz	125 / 150	51 / 53 ±2	20 / 20	550	2 HU, 430 mm	14
BSA 0125-150	9 kHz ... 250 MHz	150 / 200	51.8 / 54 ±2	20 / 20	650	3 HU, 630 mm	27
BSA 0125-200	9 kHz ... 250 MHz	200 / 220	53 / 55 ±2	20 / 20	850	3 HU, 630 mm	30
BSA 0125-250	9 kHz ... 250 MHz	250 / 300	54 / 56 ±2	20 / 20	950	3 HU, 630 mm	31
BSA 0125-300	9 kHz ... 250 MHz	300 / 350	54 / 56 ±2	20 / 20	1000	3 HU, 630 mm	34
BSA 0125-400	9 kHz ... 250 MHz	400 / 500	56 / 58 ±2	20 / 20	2000	4 HU, 630 mm	44
BSA 0125-500	9 kHz ... 250 MHz	500 / 600	57 / 59 ±2	20 / 20	2800	4 HU, 630 mm	46
BSA 0125-600	9 kHz ... 250 MHz	600 / 650	57.8 / 60 ±2	20 / 17	2800	4 HU, 630 mm	46
BSA 0125-800	9 kHz ... 250 MHz	800 / 900	59 / 61 ±2	20 / 20	3500	5 HU, 630 mm	62
BSA 0125-1000/800	9 kHz ... 250 MHz				3500	5 HU, 630 mm	65
	9 kHz ... 200 MHz	1000 / 1200	60 / 62 ±2	20 / 20			
	200 ... 250 MHz	800 / 1000	59 / 61 ±2	20 / 20			
BSA 0125-1000	9 kHz ... 250 MHz	1000 / 1100	60 / 62 ±2	20 / 18	3500	5 HU, 630 mm	65
BSA 0125-1250	9 kHz ... 250 MHz	1250 / 1350	61 / 63 ±2	20 / 18	7500	10 HU, 630 mm	110
BSA 0125-2000	9 kHz ... 250 MHz	2000 / 2200	63 / 65 ±2	20 / 18	14000	18 HU, 800 mm	180

For individual data sheets, please click on the above model name

1 HU = 44.45 mm