

STANDARD MODELS

| Model          | Frequency Range  | Output Power<br>P <sub>p</sub> min / Duty<br>W <sub>pk</sub> / % | Pulse Width<br>max. **) | Gain<br>typ<br>dB | Harmonics<br>2nd / 3rd<br>dBc | Line Power<br>VA | Dimensions<br>(H, D)<br>19"-System | Weight<br>kg |
|----------------|------------------|--|-------------------------|-------------------|-------------------------------|------------------|------------------------------------|--------------|
| BPA 0410-250   | 400 ... 1000 MHz | 250 / 10   | 100 µs                  | 54 ±2             | 15 / 20                       | 500              | 3 HU, 430 mm                       | 22           |
| BPA 0410-1000  | 400 ... 1000 MHz | 1000 / 10  | 100 µs                  | 60 ±2             | 15 / 20                       | 900              | 4 HU, 630 mm                       | 32           |
| BPA 0410-1200  | 400 ... 1000 MHz | 1200 / 10  | 100 µs                  | 61 ±2             | 15 / 20                       | 1000             | 5 HU, 630 mm                       | 55           |
| BPA 0410-2000  | 400 ... 1000 MHz | 2000 / 10  | 100 µs                  | 63 ±2             | 15 / 20                       | 2000             | 9 HU, 630 mm                       | 90           |
| BPA 0410-4000  | 400 ... 1000 MHz | 4000 / 10  | 100 µs                  | 66 ±2             | 20 / 20                       | 4000             | 12 HU, 630 mm                      | 155          |
| BPA 0410-10000 | 400 ... 1000 MHz | 10000 / 4  | 40 µs                   | 70 ±2             | 15 / 20                       | 4500             | 24 HU, 800 mm                      | 300          |

For individual data sheets, please click on the above model name 1 HU = 44.45 mm