

BPA 1 ... 2 GHz Pulsed Solid State Amplifiers

STANDARD MODELS

Model	Frequency Range	Output Power P _p min / Duty W _{pk} / %	Pulse Width max. **)	Gain typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BPA 1020-250	1 ... 2 GHz	250 / 10	100 µs	54 ±3	15 / 15	500	3 HU, 430 mm	22
BPA 1020-1000	1 ... 2 GHz	1000 / 10	100 µs	60 ±3	15 / 15	900	4 HU, 630 mm	37
BPA 1020-2000	1 ... 2 GHz	2000 / 10	100 µs	63 ±3	15 / 15	2000	7 HU, 630 mm	75
BPA 1020-4000	1 ... 2 GHz	4000 / 10	100 µs	66 ±3	12 / 20	4000	12 HU, 800 mm	150
BPA 1020-8000	1 ... 2 GHz	8000 / 10	100 µs	69 ±3	12 / 20	7500	21 HU, 800 mm	220
BPA 1020-11000	1 ... 2 GHz	11000 / 10	100 µs	70.4 ±3	10 / 20	12000	32 HU, 800 mm	450

For individual data sheets, please click on the above model name 1 HU = 44.45 mm