

STANDARD MODELS

| Model | Frequency Range | Output Power P _p min / Duty W _{pk} / % | Pulse Width max. **) | Gain typ dB | Harmonics 2nd / 3rd dBc | Line Power VA | Dimensions (H, D) 19"-System | Weight kg |
|---------------|-----------------|--|-------------------------|-------------------|-------------------------------|------------------|------------------------------------|--------------|
| BPA 1025-1000 | 1 ... 2.5 GHz | 1000 / 10 | 100 µs | 60 ±3 | 15 / 15 | 1500 | 4 HU, 630 mm | 37 |
| BPA 1025-2000 | 1 ... 2.5 GHz | 2000 / 10 | 100 µs | 63 ±3 | 15 / 15 | 3000 | 7 HU, 630 mm | 75 |
| BPA 1025-3000 | 1 ... 2.5 GHz | 3000 / 10 | 100 µs | 64.8 ±3 | 15 / 15 | 4500 | 10 HU, 630 mm | 110 |
| BPA 1025-4000 | 1 ... 2.5 GHz | 4000 / 10 | 100 µs | 66 ±3 | 15 / 15 | 6000 | 12 HU, 630 mm | 150 |
| BPA 1025-6000 | 1 ... 2.5 GHz | 6000 / 10 | 100 µs | 67.8 ±3 | 15 / 15 | 9000 | 18 HU, 800 mm | 200 |

For individual data sheets, please click on the above model name

1 HU = 44.45 mm