

STANDARD MODELS

Model	Part Number	Frequency Range	Coupling dB	Power Pmin W	Insertion Loss max dB	Directivity min dB	VSWR max Main Line	Main Line Connectors	Coupling Line Connector(s)
BDC 0103-40/1000	10021384	1 ... 30 MHz	40 ±0.5	1000	0.1	30	1.1:1	N-f/N-f	SMA-f
	10025830	1 ... 30 MHz	40 ±0.5	1000	0.1	30	1.1:1	N-f/N-f	N-f
BDC 0103-50/1000	10021385	1 ... 30 MHz	50 ±0.5	1000	0.1	30	1.1:1	N-f/N-f	SMA-f
BDC 0103-50/1500	10009818	1 ... 30 MHz	50 ±1.5	1500	0.2	20	1.15:1	N-f/N-f	SMA-f
	10024553	1 ... 30 MHz	50 ±1.5	1500	0.2	20	1.15:1	N-f/N-f	N-f
BDC 0103-60/1000	10021386	1 ... 30 MHz	60 ±0.5	1000	0.1	30	1.1:1	N-f/N-f	SMA-f
BDC 0103-60/15000	10012859	1 ... 30 MHz	60 ±1	15000	0.05	25	1.1:1	1 5/8"/1 5/8"	N-f

For individual data sheets, please click on the above model name