

STANDARD MODELS

Model	Part Number	Frequency Range	Coupling dB	Power Pmin W	Insertion Loss		Directivity min dB	VSWR max Main Line	Main Line Connectors	Coupling Line Connector(s)
					max dB					
BDC 0140-30/250	10013432	9 kHz ... 400 MHz	30 ±1.5	250	0.75		20	1.2:1	N-f/N-f	SMA-f
	10020420	9 kHz ... 400 MHz	30 ±1.5	250	0.75		20	1.25:1	N-m/N-f	N-f
BDC 0140-40/200	10020404	9 kHz ... 400 MHz	40 ±1.5	200	0.3		20	1.25:1	N-m/N-f	N-f
	10014999	9 kHz ... 400 MHz	40 ±1.5	200	0.3		20	1.25:1	N-f/N-f	N-f
	10014907	9 kHz ... 400 MHz	40 ±1.5	200	0.3		20	1.25:1	N-m/N-f	SMA-f
BDC 0140-40/500	10024229	9 kHz ... 400 MHz	40 ±1.5	500	0.3		20	1.3:1	N-m/N-f	N-f
	10015941	9 kHz ... 400 MHz	40 ±1.5	500	0.3		20	1.3:1	N-f/N-f	N-f
	10007964	9 kHz ... 400 MHz	40 ±1.5	500	0.3		20	1.2:1	N-f/N-f	SMA-f
BDC 0140-50/200	10024985	9 kHz ... 400 MHz	50 ±1.5	200	0.2		20	1.3:1	N-f/N-f	N-f
BDC 0140-50/500	10024026	9 kHz ... 400 MHz	50 ±1.5	500	0.2		20	1.3:1	N-f/N-f	SMA-f
	10024230	9 kHz ... 400 MHz	50 ±1.5	500	0.2		20	1.3:1	N-f/N-f	N-f
	10021107	9 kHz ... 400 MHz	50 ±1.5	500	0.2		20	1.3:1	N-m/N-f	N-f

For individual data sheets, please click on the above model name