

STANDARD MODELS

Model	Frequency Range	Power CW min W	Attenuation nom / Variation dB	VSWR max	Input Connector	Output Connector	Dimensions (L, W, H) mm	Weight kg	Part Number
BCA 0018-20/25	DC ... 18 GHz	25	20±0.75	1.35:1	N-m	N-f	46 / 38.1 / 38.1	0.11	10021877
BCA 0018-20/50	DC ... 18 GHz	50	20±0.75	1.35:1	N-m	N-f	101.7 / 38.1 / 38.1	0.21	10021878
BCA 0018-30/250	DC ... 18 GHz	250	30 -2.5/+4.0	1.6:1	N-m	N-f	390 / 76 / 97	1.4	10019833
BCA 0018-30/250	DC ... 18 GHz	250	30 -2.5/+4.0	1.6:1	N-f	N-f	390 / 76 / 97	1.4	10019833
BCA 0018-30/500	DC ... 18 GHz	500	30±3	1.5:1	N-m	N-f	509 / 110 / 120	6	10020635
BCA 0018-40/100	DC ... 18 GHz	100	40±0.75	1.45:1	N-m	N-f	211 / 38.1 / 38.1	7.4	10020636
BCA 0018-40/200	DC ... 18 GHz	200	40 -2.0/+3.0	1.5:1	N-m	N-f	321.7 / 63.5 / 63.5	1.01	10021429
BCA 0018-40/250	DC ... 18 GHz	250	40 -2.5/+4.0	1.6:1	N-m	N-f	390 / 76 / 97	1.4	10020618

For individual data sheets, please click on the above model name

Dimensions without connectors